


MACWHYTE Torque-Balanced™ Wire Rope


Offers the highest strength-to-weight ratio available for marine and oceanographic applications.

SPECIFY: Bright, Galvanized or Jacketed Wire Rope.

Size Inches	Construction	Weight In Air Lbs./Ft.	Approx. Elastic Limit Lbs.	Minimum Breaking Load Lbs.	0.2% Yield Strength Lbs.	Maximum Length Feet
3/16	3x19 Seale	.0586	3,000	4,000	3,500	50,000
1/4	3x19 Seale	.0997	5,063	6,750	5,900	45,000
5/16	3x19 Seale	.153	7,725	10,300	9,100	30,000
3/8	3x19 Seale	.220	11,100	14,800	13,000	50,000
7/16	3x19 Seale	.304	15,000	20,000	17,600	42,000
1/2	3x19 Seale	.392	19,275	25,700	22,600	98,000
9/16	3x19 Seale	.492	24,375	32,500	28,600	77,000
5/8	3x19 Seale	.602	30,225	40,300	35,500	62,000
3/4	3x19 Seale	.879	43,350	57,800	50,900	43,000
7/8	3x19 Seale	1.21	58,500	78,000	68,600	32,000
1	3x19 Seale	1.56	75,450	100,600	88,500	24,000
1-1/8	3x19 Seale	1.96	93,000	124,000	109,000	19,000
1/2	3x41 Seale FW	.417	19,275	25,700	22,600	98,000
9/16	3x41 Seale FW	.517	24,375	32,500	28,600	77,000
5/8	3x41 Seale FW	.631	30,225	40,300	35,500	62,000
3/4	3x46 Seale FW	.903	43,350	57,800	50,900	43,000
7/8	3x46 Seale FW	1.27	58,500	78,000	68,600	32,000
1	3x46 Seale FW	1.64	75,450	100,600	88,500	24,000
1-1/8	3x46 Seale FW	2.07	93,000	124,000	109,000	19,000
1-1/4	3x46 Seale FW	2.60	118,500	158,000	139,000	15,500
1-3/8	3x46 Seale FW	3.10	141,000	188,000	165,000	12,900
1-1/2	3x46 Seale FW	3.69	166,500	222,000	195,000	10,800



3 x 19



3 x 46

Notices: Published breaking strengths apply only to new, unused wire rope. Any performance specifications are conditional on proper rope size, construction, and grade; on proper design and maintenance of mechanical equipment on which wire rope products are used; and on proper storage, handling, use, maintenance and periodic inspection of such products during the period of use. In all cases the terms and conditions of sale in effect at the time of sale shall govern the Company's obligation to repair or replace defective products and the extent of its liability therefore.



Macwhyte Wire Rope Company

2906-14th Avenue
Kenosha, Wisconsin 53141
(414) 654-5381
Fax: (414) 654-5384

ONE OF THE **Amsted**
INDUSTRIES